

BioMini Slim 2

Ultra-slim FAP20 Authentication Scanner



BioMini Slim 2 is FAP20 certified fingerprint scanner featuring an array of cutting-edge technologies. Along with its 13.5mm slim optical sensor, BioMini Slim 2 features Suprema's proprietary Multi-dynamic Range(MDR) technology, FBI PIV and Mobile ID FAP20 compliance and Android device support. BioMini Slim 2 also provides developers more physical flexibility with its reduced form factor and the ultra-slim optical sensor ensures robust operation over time. BioMini Slim provides new and advanced Live Finger Detection(LFD) technology by applying a machine learning method that analyzes and categorizes image patterns according to optical characteristics.



BioMini Slim 2

Ultra-slim FAP20 Authentication Scanner

FEATURES



· World's slimmest FAP 20 optical sensor



- · FBI PIV and FBI Mobile ID FAP20 certificates
- · Image compression standard: WSQ



- · Capturing high-quality fingerprint images even when the finger is dry & wet.
- · Operates under direct sunlight up to 100,000 LUX



- \cdot Live Fingerprint Detection (LFD) Technology
- Distinguishes fake fingerprints made from various materials including clay, rubber, silicon, glue, paper, film and more



- · Easy Integration
- BioMini SDK for easy application development
- Android, MS Windows & Linux compatible
- Multi-threaded code design for multi-core CPU utilization



- \cdot No need to type in a password
- · Instant login by touching your finger

SPECIFICATIONS

Android			
Sensor Type	Sensor	Image Quality Standards	FBI PIV / FBI Mobile ID FAP20
Resolution 500 ppi Image Grayscale 8 bit, 256 levels Platen Size (Wx L mm) 16.5 x 21.0 Sensing Area (Wx H mm) 15.24 x 20.32 Image Size (Wx H pixels) 300 x 400 Interface USB 2.0 High Speed Sensor Surface Optic Glass, Scratch-free Operating Temperature(°C) -10~50°C Operating humidity 0~90% RH Ingress Protection IP65 (Sensor Surface) Dimensions (Wx L x H mm) 72.8 x 40.7 x 18.5 Weight 91g Windows Windows XP, Vista, 7, 8, 8.1, 10 32/64bit Linux Ubuntu, Debian, Fedora, OpenSUSE, Cent OS 32/64b Android Android 4.1(Jelly Bean)and Above O Image Format RAW, BMP, WSQ, ISO 19794-4 Template Type Suprema, ISO19794-2, ANSI-378 CE O FCC O KC O RoHS O UL X USB-IF X CB O IEC62471 O WEEE O REACH O		Live Finger Detection	0
Image Grayscale		Sensor Type	Optical
Platen Size (Wx L mm)		Resolution	500 ppi
Sensing Area (W x H mm) 15.24 x 20.32 Image Size (W x H pixels) 300 x 400 Interface		Image Grayscale	8 bit, 256 levels
Image Size (Wx H pixels) 300 x 400 Interface USB 2.0 High Speed Sensor Surface Optic Glass, Scratch-free Operating Temperature(°C) -10-50°C Operating humidity 0 ~ 90% RH Ingress Protection IP65 (Sensor Surface) Dimensions (Wx L x H mm) 72.8 X 40.7 X 18.5 Weight 91g Windows Windows XP, Vista, 7, 8, 8.1, 10 32/64bit Linux Ubuntu, Debian, Fedora, OpenSUSE, Cent OS 32/64b Android Android 4.1(Jelly Bean) and Above O Image Format RAW, BMP, WSQ, ISO 19794-4 Template Type Suprema, ISO19794-2, ANSI-378 CE O FCC O KC O ROHS O UL X USB-IF X CB O IEC62471 O WEEE O REACH O		Platen Size (W x L mm)	16.5 x 21.0
Interface USB 2.0 High Speed Sensor Surface Optic Glass, Scratch-free Operating Temperature(°C) -10~50°C Operating humidity 0~90% RH Ingress Protection IP65 (Sensor Surface) Dimensions (Wx L x H mm) 72.8 X 40.7 X 18.5 Weight 91g Windows Windows XP, Vista, 7, 8, 8.1, 10 32/64bit Linux Ubuntu, Debian, Fedora, OpenSUSE, Cent OS 32/64b Android Android Android Android 4.1(Jelly Bean)and Above Image Format RAW, BMP, WSQ, ISO 19794-4 Template Type Suprema, ISO19794-2, ANSI-378 CE O FCC O KC O RoHS O UL X USB-IF X CB O IEC62471 O WEEE O REACH O		Sensing Area (W x H mm)	15.24 x 20.32
Sensor Surface Operating Temperature(°C) -10~50°C Operating Mumidity Ingress Protection Dimensions (Wx L x H mm) S/W Android Android 4.1(Jelly Bean)and Above Template Type CE OFCC O KC ROHS OUL X USB-IF CB REACH OPERATING MUMID OPTION CHARLES		Image Size (W x H pixels)	300 x 400
Operating Temperature(°C)	H/W	Interface	USB 2.0 High Speed
H/W Operating humidity 0 ~ 90% RH Ingress Protection IP65 (Sensor Surface) Dimensions (Wx L x H mm) 72.8 X 40.7 X 18.5 Weight 91g Windows Windows XP, Vista, 7, 8, 8.1, 10 32/64bit Linux Ubuntu, Debian, Fedora, OpenSUSE, Cent OS 32/64b Android A.1(Jelly Bean) and Above RAW, BMP, WSQ, ISO 19794-4 Template Type Suprema, ISO19794-2, ANSI-378 CE		Sensor Surface	Optic Glass, Scratch-free
Ingress Protection		Operating Temperature(°C)	-10~50°C
Dimensions (WxLxHmm) 72.8 X 40.7 X 18.5		Operating humidity	0 ~ 90% RH
Weight 91g		Ingress Protection	IP65 (Sensor Surface)
Windows Windows XP, Vista, 7, 8, 8.1, 10 32/64bit		Dimensions (WxLxHmm)	72.8 X 40.7 X 18.5
Linux		Weight	91g
S/W Android	S/W	Windows	Windows XP, Vista, 7, 8, 8.1, 10 32/64bit
Android 4.1(Jelly Bean) and Above Image Format RAW, BMP, WSQ, ISO 19794-4 Template Type Suprema, ISO19794-2, ANSI-378 CE FCC O KC O RoHS UL X USB-IF CB O IEC62471 WEEE O REACH		Linux	Ubuntu, Debian, Fedora, OpenSUSE, Cent OS 32/64bit
Template Type Suprema, ISO19794-2, ANSI-378 CE O FCC O KC O RoHS O UL X USB-IF X CB O IEC62471 O WEEE O REACH O			0
CE		Image Format	RAW, BMP, WSQ, ISO 19794-4
FCC O C C C C C C C C C C C C C C C C C		Template Type	Suprema, ISO19794-2, ANSI-378
KC	Certification	CE	0
RoHS		FCC	0
UL X USB-IF X CB O IEC62471 O WEEE O REACH O		KC	0
USB-IF X CB O IEC62471 O WEEE O REACH O		RoHS	0
CB O IEC62471 O WEEE O REACH O		UL	X
IEC62471 O WEEE O REACH O		USB-IF	X
WEEE O REACH O		СВ	0
REACH O		IEC62471	0
nate:		WEEE	0
WHQL		REACH	0
		WHQL	0



Suprema ID Inc.