



Insured amounts
page 04

Fig. Wall safe AMS0600, hinge right
K-Lock Cawi 2 keys (95 mm), 1 shelf

[Wall safes]

[Type AMS]

AMS series wall safes are designed for installation into suitable masonry. They are set into the wall so that the front (the door) is aligned with the wall and the body is encased with a minimum of 10 cm of concrete. The optional rear wall armouring allows a wall thickness equivalent to the safe depth.

[Product information]

Hinge	DIN right (internal) – model designation R option: DIN left
Door opening angle	95°
Body	hot galvanised steel plate construction to resist corrosion
Door structure	triple-walled, massive steel design, internal boltwork protected by sheets of hardened steel to give extra anti-drill resistance
Locking mechanism	three-way moving boltwork with large steel bolts protected by additional emergency re-lockers, continuous fixed full height bolt on the hinge side
Colour	inside and outside RAL 7037 dusty grey option: special colour according to RAL
Lock page 30, 31	model designation K – double-bit lock VdS class 1, Cawi 2 keys (95 mm) model designation E – electronic lock VdS class 2, M-locks EM3520 option: other lock models (primary lock or possible secondary lock)
Equipment page 32	shelf adjustable (height setting 80 mm) option: additional shelf option (only at models with outside depth 380 mm): inside locker
Accessories page 33	option: rear wall armor, interior lighting
Note	models AMS0401, AMS0601, AMS0801, AMS1001 do not offer enough depth for file folders DIN A4, one file folder can be stored behind the door

Model	Outside dimensions h x w x d (mm)	Inside dimensions h x w x d (mm)	SH	Volume (l)	Weight (appr. kg)
AMS0400RK / AMS0400RE	410 x 510 x 380	360 x 460 x 295	1	49	50
AMS0401RK / AMS0401RE	410 x 510 x 230	360 x 460 x 145	1	24	45
AMS0600RK / AMS0600RE	590 x 510 x 380	540 x 460 x 295	1	73	65
AMS0601RK / AMS0601RE	590 x 510 x 230	540 x 460 x 145	1	36	60
AMS0800RK / AMS0800RE	770 x 510 x 380	720 x 460 x 295	1	98	80
AMS0801RK / AMS0801RE	770 x 510 x 230	720 x 460 x 145	1	48	70
AMS1000RK / AMS1000RE	950 x 510 x 380	900 x 460 x 295	2	122	95
AMS1001RK / AMS1001RE	950 x 510 x 230	900 x 460 x 145	2	60	85

SH = Shelf

Please add 10 mm to the listed outside depth for mountings.

[Equipment options]

